Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 02/19/1999 Revision date: 04/22/2022 Supersedes: 04/24/2020 Version: 2.0



SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : DT61 - GLASS CLEANER CONCENTRATE

Product code : DT61

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial and Institutional Glass Cleaner Concentrate

1.3. Details of the supplier of the safety data sheet

Sky Blue Chemical 760 W. Exchange Road Ogden, Utah 84401 - USA T (801) 394-8611

www.skybluechemical.com

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Liq. 3 H226 Skin Irrit. 2 H315 Eye Irrit. 2 H319

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)





GHS02

Signal word (GHS US) : Warning

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H319 - Causes serious eye irritation

Precautionary statements (GHS US)

Prevention : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response : P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use media other than water to extinguish.

Storage : P403+P235 - Store in a well-ventilated place. Keep cool.

05/04/2022 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Disposal

: P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

2.4. Unknown acute toxicity (GHS US)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Isopropyl alcohol	(CAS-No.) 67-63-0	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
butyl glycolether	(CAS-No.) 111-76-2	5 – 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin

irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: All extinguishing media allowed. Adapt extinguishing media to the environment. Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.
Reactivity : Flammable liquid and vapor.

5.3. Advice for firefighters

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. Use personal protective equipment (PPE). No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

05/04/2022 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological information.

Methods and material for containment and cleaning up

Methods for cleaning up

: Take up liquid spill into absorbent material. Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Notify authorities if product enters sewers or public

Other information

Dispose of contents/container to {0|message=<specify in accordance with local/regional/national/international regulations>|default=hazardous or special waste collection point, in accordance with local, regional, national and/or international

regulation|filter=^(_)?DISPOSAL_.+}. Dispose of materials or solid residues at an authorized

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Ensure good ventilation of the work station. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only nonsparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.

Hygiene measures

Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment.

Storage conditions Incompatible products Store in a well-ventilated place. Keep cool. Keep container tightly closed.

: Strong acids. Strong bases. Strong oxidizing agents.

SECTION 8: Exposure controls/personal protection

Control parameters

butyl glycolether (111-76-2)				
ACGIH	ACGIH OEL TWA [ppm]	20 ppm		
ACGIH	Remark (ACGIH)	Eye & URT irr		
OSHA	OSHA PEL (TWA) [1]	240 mg/m³		
OSHA	OSHA PEL (TWA) [2]	50 ppm		
Isopropyl alcohol (67-63-0)	Isopropyl alcohol (67-63-0)			
ACGIH	ACGIH OEL TWA [ppm]	200 ppm		
ACGIH	ACGIH OEL STEL [ppm]	400 ppm		
ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair		
OSHA	OSHA PEL (TWA) [1]	980 mg/m³		
OSHA	OSHA PEL (TWA) [2]	400 ppm		

Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection Protective gloves. Eye protection Safety glasses.

Skin and body protection Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Avoid release to the environment. Environmental exposure controls

05/04/2022 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

No data availableNo data available

No data available

Odor threshold : No data available

Melting point : Not applicable
Freezing point : No data available

Boiling point : No data available
Flash point : ≈ 35 °C (estimated)
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Not applicable.
Vapor pressure : No data available

Relative vapor density at 20 °C : No data available

Relative density : 0.96 Density 8.02 lb/gal Solubility : Soluble in water. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature : No data available Viscosity, kinematic Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

VOC content : 22.7 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

05/04/2022 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)			
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)		
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))		
ATE US (oral)	1746 mg/kg body weight		
ATE US (dermal)	435 mg/kg body weight		
ATE US (gases)	4500 ppmV/4h		
ATE US (vapors)	11 mg/l/4h		
ATE US (dust, mist)	1.5 mg/l/4h		
Isopropyl alcohol (67-63-0)			
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))		
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))		
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value Inhalation (vapours), 14 day(s))		
ATE US (oral)	5840 mg/kg body weight		
ATE US (dermal)	16400000 mg/kg body weight		
Skin corrosion/irritation	: Causes skin irritation.		
Serious eye damage/irritation	: Causes serious eye irritation.		
Respiratory or skin sensitization	: Not classified		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
butyl glycolether (111-76-2)			
IARC group	3 - Not classifiable		
Isopropyl alcohol (67-63-0)			
IARC group	3 - Not classifiable		
Reproductive toxicity	: Not classified		
STOT-single exposure	: Not classified		
STOT-repeated exposure	: Not classified		
Aspiration hazard	: Not classified		
Symptoms/effects after skin contact	: Irritation.		
Symptoms/effects after eye contact	: Eye irritation.		

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

butyl glycolether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	911 mg/l (72 Hr.)
Isopropyl alcohol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

12.2. Persistence and degradability

butyl glycolether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance

05/04/2022 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)			
ThOD	2.305 g O ₂ /g substance		
BOD (% of ThOD)	0.31		
Isopropyl alcohol (67-63-0)			
Persistence and degradability Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.			
Biochemical oxygen demand (BOD) 1.19 g O ₂ /g substance			
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance		
ThOD	2.4 g O₂/g substance		

12.3. Bioaccumulative potential

butyl glycolether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Isopropyl alcohol (67-63-0)		
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)	

12.4. Mobility in soil

butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Isopropyl alcohol (67-63-0)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN1993 Flammable liquids, n.o.s. (Isopropyl Alcohol), 3, III

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Isopropyl Alcohol

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger Hazard labels (DOT) : 3 - Flammable liquid



05/04/2022 EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 173.xxx) : 24

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

μ

Transport by sea

UN-No. (IMDG) : 1993

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Marine pollutant :

Air transport

UN-No. (IATA) : 1993

Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylene glycol	CAS-No. 107-21-1	< 1%
Isopropyl alcohol	CAS-No. 67-63-0	10 – 20%

05/04/2022 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)		
SARA Section 311/312 Hazard Classes Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard		
SARA Section 313 - Emission Reporting	1 %	
ethylene glycol (107-21-1)		
CERCLA RQ	5000 lb	
SARA Section 313 - Emission Reporting	1 %	
Isopropyl alcohol (67-63-0)		
SARA Section 313 - Emission Reporting	1 %	

15.2. International regulations

ethylene glycol (107-21-1)

Listed on EPA Hazardous Air Pollutant (HAPS)

Ethyl alcohol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

di(tetramethylammonium)(29H,31H-phthalocyanin-N29,N30,N31,N32)disulfonamide disulfonate, cuprate(2-)complex, derivates (12222-04-7)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

Proprietary Surfactants (Trade Secret)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

BLUE AGAVE

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

15.3. US State regulations

This product can expose you to ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ethylene glycol (107-21-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

butyl glycolether (111-76-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

ethylene glycol (107-21-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Isopropyl alcohol (67-63-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Ethyl alcohol (64-17-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

05/04/2022 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Propanol (71-23-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 04/22/2022

Full text of H-phrases:

t or ri prii aoco.	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation

SDS US (GHS HazCom 2012) - Custom

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

05/04/2022 EN (English US) 9/9