

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : CW31 - HIGH PH TOUCHLESS PRESOAK
 Product code : CW31

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Industrial and Institutional Alkaline Detergent

1.3. Supplier

Sky Blue Chemical
 760 W. Exchange Road
 Ogden, Utah 84401 - USA
 T (800) 998-2808
www.skybluechemical.com

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Irrit. 2 H315 Causes skin irritation
 Eye Dam. 1 H318 Causes serious eye damage

Full text of hazard classes and H-statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
 Hazard statements (GHS US) : H315 - Causes skin irritation
 H318 - Causes serious eye damage

Precautionary statements (GHS US) : P264 - Wash hands, forearms and face thoroughly after handling.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - If on skin: Wash with plenty of water.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 - Immediately call a poison center or doctor.
 P321 - Specific treatment (see supplemental first aid instruction on this label).
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Tetrasodium ethylenediaminetetraacetate	(CAS-No.) 64-02-8	1 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Sodium hydroxide	(CAS-No.) 1310-73-2	1 – 3	Met. Corr. 1, H290 Skin Corr. 1, H314 Aquatic Acute 3, H402
UNDECETH-5	(CAS-No.) 34398-01-1	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
butyl glycolether	(CAS-No.) 111-76-2	1 – 3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320
Sodium xylenesulfonate	(CAS-No.) 1300-72-7	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Call a physician immediately.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
- Symptoms/effects : Causes severe skin burns and eye damage.
- Symptoms/effects after skin contact : Burns. Irritation.
- Symptoms/effects after eye contact : Serious damage to eyes.
- Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. See Section 12 for additional Ecological information.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe fume/gas/mist/spray/vapours. Avoid contact during pregnancy/while nursing. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Wash hands and other exposed skin thoroughly after handling. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container closed when not in use. Store locked up. Store in a well-ventilated place. Keep cool.
- Incompatible products : Strong acids. Oxidizing agent.
- Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CW31 - HIGH PH TOUCHLESS PRESOAK	
No additional information available	
Sodium hydroxide (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH Ceiling (mg/m ³)	2 mg/m ³
Remark (ACGIH)	URT, eye, & skin irr
USA - OSHA - Occupational Exposure Limits	
Local name	Sodium hydroxide
OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
UNDECETH-5 (34398-01-1)	
No additional information available	
butyl glycolether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Eye & URT irr
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
OSHA PEL (TWA) (ppm)	50 ppm

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tetrasodium ethylenediaminetetraacetate (64-02-8)

No additional information available

Sodium xylenesulfonate (1300-72-7)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or face shield. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Dark green
Odor	: Detergent
Odor threshold	: No data available
pH	: > 11
pH solution	: 1 %
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 212 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 1.02 – 1.03
Density	: 8.35 lb/gal
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content : 4.2 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

UNDECETH-5 (34398-01-1)

LD50 oral rat	> 1400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

butyl glycolether (111-76-2)

LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Tetrasodium ethylenediaminetetraacetate (64-02-8)

LD50 oral rat	1780 – 2000 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	4.14 mg/l/4h Dust

Sodium xylenesulfonate (1300-72-7)

LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 6.41 mg/l (Equivalent or similar to OECD 403, 232 minutes, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation : Causes skin irritation.
pH: > 11

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation	: Causes serious eye damage. pH: > 11
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

butyl glycolether (111-76-2)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Sodium xylenesulfonate (1300-72-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after skin contact : Burns. Irritation.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Sodium hydroxide (1310-73-2)

LC50 fish 1	189 mg/l (48 h, <i>Leuciscus idus</i> , Fresh water, Experimental value)
-------------	--

EC50 Daphnia 1	40.4 mg/l (48 h, <i>Ceriodaphnia sp.</i> , Experimental value, Locomotor effect)
----------------	--

UNDECETH-5 (34398-01-1)

LC50 fish 1	1 – 10 mg/l (96 hr.)
-------------	----------------------

EC50 Daphnia 1	1 – 10 mg/l (48 hr.)
----------------	----------------------

EC50 other aquatic organisms 1	1 – 10 mg/l (96 hr.)(Algae)
--------------------------------	-----------------------------

butyl glycolether (111-76-2)

LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, <i>Oncorhynchus mykiss</i> , Static system, Fresh water, Experimental value, Lethal)
-------------	--

EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Locomotor effect)
----------------	--

ErC50 (algae)	911 mg/l (72 Hr.)
---------------	-------------------

Tetrasodium ethylenediaminetetraacetate (64-02-8)

LC50 fish 1	121 mg/l (US EPA, 96 h, <i>Lepomis macrochirus</i> , Static system, Fresh water, Experimental value, Soft water)
-------------	--

EC50 Daphnia 1	625 mg/l (DIN 38412-11, 24 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Locomotor effect)
----------------	--

ErC50 (algae)	> 100 mg/l (EU Method C.3, 72 h, <i>Desmodesmus subspicatus</i> , Static system, Fresh water, Weight of evidence, Nominal concentration)
---------------	--

Sodium xylenesulfonate (1300-72-7)

LC50 fish 1	> 1000 mg/l (EPA OTS 797.1400, 96 h, <i>Oncorhynchus mykiss</i> , Static system, Fresh water, Experimental value)
-------------	---

EC50 Daphnia 1	> 1000 mg/l (EPA OTS 797.1300, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value)
----------------	---

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

CW31 - HIGH PH TOUCHLESS PRESOAK	
Persistence and degradability	Not established.
Sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
butyl glycoether (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O ₂ /g substance
Sodium xylenesulfonate (1300-72-7)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

CW31 - HIGH PH TOUCHLESS PRESOAK	
Bioaccumulative potential	Not established.
Sodium hydroxide (1310-73-2)	
Bioaccumulative potential	Not bioaccumulative.
butyl glycoether (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
BCF fish 1	1.1 – 1.8 (28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-13.17 (Estimated value, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Sodium xylenesulfonate (1300-72-7)	
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Sodium hydroxide (1310-73-2)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.
butyl glycoether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Tetrasodium ethylenediaminetetraacetate (64-02-8)	
Partition coefficient n-octanol/water (Log Koc)	2.495 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
Sodium xylenesulfonate (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium xylenesulfonate (1300-72-7)	
Partition coefficient n-octanol/water (Log Koc)	1.42 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local/state/federal regulations..
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3266 Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide), 8, III
UN-No.(DOT) : UN3266
Proper Shipping Name (DOT) : Corrosive liquid, basic, inorganic, n.o.s.
Sodium hydroxide
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Symbols : G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids
Other information : No supplementary information available.

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Acetaldehyde	CAS-No. 75-07-0	< 0.1%
Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Ethylene oxide	CAS-No. 75-21-8	< 0.1%
Acetaldehyde	CAS-No. 75-07-0	< 0.1%
ethylene glycol	CAS-No. 107-21-1	< 0.1%
Sodium hydroxide (1310-73-2)		
CERCLA RQ	1000 lb	
UNDECETH-5 (34398-01-1)		
EPA TSCA Regulatory Flag	N - N - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used. P - P - indicates a commenced Premanufacture Notice (PMN) substance. XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Ethylene oxide (75-21-8)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	10 lb	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb	
Acetaldehyde (75-07-0)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	1000 lb	
butyl glycolether (111-76-2)		
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
ethylene glycol (107-21-1)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	5000 lb	
Tetrasodium ethylenediaminetetraacetate (64-02-8)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	

15.2. International regulations

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene oxide (75-21-8)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)

Acetaldehyde (75-07-0)

Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Sodium hydroxide(1310-73-2)	U.S. - New Jersey - Right to Know Hazardous Substance List
Ethylene oxide(75-21-8)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetaldehyde(75-07-0)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
butyl glycoether(111-76-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
ethylene glycol(107-21-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Sodium sulfate(7757-82-6)	U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 02/18/2022

Other information : None.

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1	Skin corrosion/irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation
H318	Causes serious eye damage

SDS US (GHS HazCom 2012)

CW31 - HIGH PH TOUCHLESS PRESOAK

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.